



TACK TAG 2



FUNCTIONALITY

RF Protocol:	EPC Class 1 Gen 2; ISO 18000-6C
Operating Frequency:	US: 902 to 238 MHz
Memory Configuration:	96-Bit EPC; 512 User Bit Memory; 64-Bit TID
R/W Capability:	Read/Write

PERFORMANCE

Read Range:	Up to 7 feet (with handheld reader)
Quality Guarantee:	100%
Orientation:	Readable in 360° - Range varies with orientation
IP Rating:	IP68

PHYSICAL

Material:	Stainless Steel
Mounting System:	Adhesive, Welding

OPERATIONAL

Max Temperature Exposure:	300°F/ 150°C
Min Temperature Exposure:	-40°F/ -40°C
Continuous Max Service Temperature:	300°F/ 150°C
Continuous Min Service Temperature:	-40°F/ -40°C
Water and Ice Proof:	Yes (Not for continuous immersion)

DIMENSIONS

Weight:	8.5g / 0.28 oz
Dimensions:	0.59" x 0.96"
Thickness:	0.23"



RECOMMENDED TAG APPLICATIONS

Oil & Gas: Industrial Equipment, Tools & Machinery

Visit www.infochip.com to view our demo videos and learn more about the InfoChip suite of tags, readers and asset management software. For pricing and details, please email sales@infochip.com or call Toll Free 1-844-414-8247 in the US or 1-877-747-2447 in Canada or the US.

Where is it?

What is it?

Is it safe to use?

(877) 747-2447

sales@infochip.com

www.infochip.com